128, av. du Maréchal-de-Lattre-de-Tassigny - 87045 LIMOGES Cedex
Tel: +33(0)5 55 06 87 87 - Fax: +33(0)5 55 06 88 88
www.legrand.com

Mosaic™
2P+E Flush socket outlets
French/Belgian standard

Cat. No(s): 0 771 11L - 0 771 81L - 0 791 21L
0 793 42



0 771 11L
0 791 21L



0 771 81L

1. USE

Shuttered 2P+E Flush socket outlets.
Easy to clean and prevent accumulation of dirt.
Flush or surface-mounting.
For installation in flush-mounting box 40 mm deep (minimum recommended).

2. RANGE

Description	White	Aluminium	Matt black
2P+E Flush - 2 modules	0 771 11L	0 793 42	0 791 21L
2P+E Flush - 2 modules Product supplied complete	0 771 81L	-	-

3. DIMENSIONS (mm)



Cat. Nos.	A	B	C	D
0 771 11L - 0 792 21L - 0 793 42	45	45	38.5	8.5
0 771 81L	82	82	38.5	10

4. CONNECTION

Type of terminals: automatic
Number of terminals: 3 inputs, 3 outputs
Terminal capacity: 2 x 2.5 mm^2
Stripping length: 12 mm

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics
Penetration by solid/liquid matter: IP 40 for assembled product
Impact resistance: IK 04

■ 5.2 Material characteristics
Mechanism casing: PC

Cover plate: White RAL 9003 ABS + PC
Painted glittery varnished aluminium ABS + PC
Painted satin-finish Matt black RAL 9017 ABS + PC

Halogen-free
UV-resistant

Self-extinguishing:
850°C/30 s for insulating components holding live parts in place.
650°C/30 s for other insulating components.

■ 5.3 Electrical characteristics
Current: 16 A
Voltage: 250 V~

■ 5.4 Climate characteristics
Storage temperature: -10°C to +70°C
Usage temperature: -5°C to +35°C

6. CARE

Clean the surface with a cloth.
Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Resistance to the following cleaning products: Hexane (NF C 61-314), methylated spirit, soapy water, diluted ammonia, bleach diluted to 10%, window-cleaning products, pre-impregnated wipes.

Caution: Always test before using other special cleaning products.

7. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards.
See e-catalogue.